

オールステンレス製ワンタッチ継手
全不锈钢快速接头



CAD数据文件夹名: 48_Fittings_Vacuum_Pads

请按照选型步骤①~③选择型式和参数后进行订购。

Order 订货范例
型式 (①Type · ②D) — ③公称型号
MLELLSS4 — 2
MLBULSS10

■外螺纹接头 MLCNLSS

■外螺纹弯头 MLELLSS

■直管接头型 UNSTLS

■三通管接头 UNTELS

■弯管接头 UNEBLS

■球阀 MLBULSS

■色型式

■规格

型式 ①Type	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
MLCNLSS	4	M5	21.5	10	18.5	M5×0.8	26.8
		1	21	10	17	R1/8	27.6
		2	19.5	14	14	R1/4	33.9
	6	M5	23.5	12	21.5	M5×0.8	26.7
		1	23	12	19	R1/8	27.5
		2	23.5	14	17	R1/4	35.0
	8	3	21	17	15	R3/8	45.0
		1	27.5	14	23.5	R1/8	38.0
		2	26.5	14	21	R1/4	41.7
	10	3	22	17	16	R3/8	53.5
		2	32.5	17	24	R1/4	60.1
		3	28.5	17	22.5	R3/8	68.6
MLELLSS	4	M5	22.5	12	20.5	M5×0.8	6.5
		1	24.5	12	20.5	R1/8	8.9
		2	27.5	14	22	R1/4	14.8
	6	M5	23.5	12	21.5	M5×0.8	9.8
		1	25.5	12	21.5	R1/8	10.9
		2	28.5	14	23	R1/4	16.0
	8	3	29.5	17	23.5	R3/8	23.9
		1	26.5	14	22.5	R1/8	17.6
		2	29.5	14	24	R1/4	18.4
	10	3	31.5	17	25.5	R3/8	23.1
		2	31.5	17	26	R1/4	23.6
		3	36	22	28.5	R1/2	44.8
UNSTLS	4	M5	34	10	11.5		11.5
		1	37	12	12		15.8
		2	40	14	14		21.3
	6	M5	45	17	34.3		34.3
		1	48	20	22		47.0
		2	37.5	22	22.5		46.4
UNTELS	4	M5	19	12	29.8		29.8
		1	21.5	12	29.7		29.7
		2	24	14	42.3		42.3
	6	M5	27.5	17	66.4		66.4
		1	30	22	124.6		124.6
		2	27.5	17	66.4		66.4
UNEBLS	4	M5	19	12	23.2		23.2
		1	21.5	12	23.1		23.1
		2	24	14	32.5		32.5
	6	M5	27.5	17	57.1		57.1
		1	30	22	107.0		107.0
		2	27.5	17	57.1		57.1
MLBULSS	4	M5	33.5	14	18.8		18.8
		1	36.5	17	29.3		29.3
		2	40.5	19	38.0		38.0
	6	M5	45.5	23	63.5		63.5
		1	48.5	26	79.3		79.3
		2	45.5	23	63.5		63.5

型式 ①Type	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
MLCNLSS	4	M5	21.5	10	18.5	M5×0.8	26.8
		1	21	10	17	R1/8	27.6
		2	19.5	14	14	R1/4	33.9
	6	M5	23.5	12	21.5	M5×0.8	26.7
		1	23	12	19	R1/8	27.5
		2	23.5	14	17	R1/4	35.0
	8	3	21	17	15	R3/8	45.0
		1	27.5	14	23.5	R1/8	38.0
		2	26.5	14	21	R1/4	41.7
	10	3	22	17	16	R3/8	53.5
		2	32.5	17	24	R1/4	60.1
		3	28.5	17	22.5	R3/8	68.6

型式 ①Type	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
MLELLSS	4	M5	22.5	12	20.5	M5×0.8	6.5
		1	24.5	12	20.5	R1/8	8.9
		2	27.5	14	22	R1/4	14.8
	6	M5	23.5	12	21.5	M5×0.8	9.8
		1	25.5	12	21.5	R1/8	10.9
		2	28.5	14	23	R1/4	16.0
	8	3	29.5	17	23.5	R3/8	23.9
		1	26.5	14	22.5	R1/8	17.6
		2	29.5	14	24	R1/4	18.4
	10	3	31.5	17	25.5	R3/8	23.1
		2	31.5	17	26	R1/4	23.6
		3	36	22	28.5	R1/2	44.8

型式 ①Type	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
UNSTLS	4	M5	34	10	11.5		11.5
		1	37	12	12		15.8
		2	40	14	14		21.3
	6	M5	45	17	34.3		34.3
		1	48	20	22		47.0
		2	37.5	22	22.5		46.4
UNTELS	4	M5	19	12	29.8		29.8
		1	21.5	12	29.7		29.7
		2	24	14	42.3		42.3
	6	M5	27.5	17	66.4		66.4
		1	30	22	124.6		124.6
		2	27.5	17	66.4		66.4
UNEBLS	4	M5	19	12	23.2		23.2
		1	21.5	12	23.1		23.1
		2	24	14	32.5		32.5
	6	M5	27.5	17	57.1		57.1
		1	30	22	107.0		107.0
		2	27.5	17	57.1		57.1
MLBULSS	4	M5	33.5	14	18.8		18.8
		1	36.5	17	29.3		29.3
		2	40.5	19	38.0		38.0
	6	M5	45.5	23	63.5		63.5
		1	48.5	26	79.3		79.3
		2	45.5	23	63.5		63.5

型式 ①Type	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
MLCNLSS	4	M5	21.5	10	18.5	M5×0.8	26.8
		1	21	10	17	R1/8	27.6
		2	19.5	14	14	R1/4	33.9
	6	M5	23.5	12	21.5	M5×0.8	26.7
		1	23	12	19	R1/8	27.5
		2	23.5	14	17	R1/4	35.0
	8	3	21	17	15	R3/8	45.0
		1	27.5	14	23.5	R1/8	38.0
		2	26.5	14	21	R1/4	41.7
	10	3	22	17	16	R3/8	53.5
		2	32.5	17	24	R1/4	60.1
		3	28.5	17	22.5	R3/8	68.6

耐熱ワンタッチ継手
耐热快速接头



CAD数据文件夹名: 48_Fittings_Vacuum_Pads

请按照选型步骤①~③选择型式和参数后进行订购。

Order 订货范例
型式 (①Type · ②D) — ③公称型号
KPMCS6 — 1

■耐热快速接头 一直接头 — KPMCS

■耐热快速接头 一弯管型 — KPMCL

■耐热快速接头 一带内六角孔直接头 — KPMCC

■高耐热快速接头 一直接头 — KKMCS

■高耐热快速接头 一弯管型 — KKMCL

■色型式

■规格

Type	D	型号	M	A	B	L	C1	C2	E	对边距离H	有效截面积(mm²)	重量(g)	
KPMCS	4	M5	M5×0.8	22.7				3	19.7	10	2	12	
		1	R1/8	23.7	17.6	15	8	19.7	10	4.5	13		
	2	R1/4	26.7			11	20.7	14		22			
	6	M5	M5×0.8	25.5				3	22.5	12	2	17	
		1	R1/8	25.1	19.5	16	8	21.1		11	23		
	2	R1/4	29.1			11	23.0	14		23			
	8	3	R3/8	29.9			12	22.7	17		27		
		1	R1/8	29.9			8	25.9		14	34		
	2	R1/4	28.6	20.2	17	11	22.6		20	25			
	3	R3/8	28.9			12	22.6	17		32			
	10	1	R1/8	33.3			8	29.3		17	23	40	
		2	R1/4	31.8	23.2	19.5	11	27.3			39		
KPMCL	4	M5	M5×0.8	22.7				3	19.6	10	1.5	18	
		1	R1/8	23.7	17.6	15	8	19.7	20.7	10	3.5	31	
	2	R1/4	24.7			11	18.7		14		21		
	6	M5	M5×0.8	25.5				3	22.5	12	1.9	26	
		1	R1/8	25.1	19.4	16	8	21.1	23	12	9	36	
	2	R1/4	29.1			11	23.0		17		28		
	8	3	R3/8	29.9			12	22.7		17		49	
		1	R1/8	8	28	31.3						36	
	2	R1/4	11	31	32.2	20.2	17	24.8	14	16	41		
	3	R3/8	12	32.8	33.7				17		55		
	10	1	R1/8	8	32.5	37.8					22.5	67	
		2	R1/4	11	35.5	38.8	23.2	19.5	29.3	17		69	
KPMCC	4	M5	M5×0.8	22.6				3	19.6	2	2	11	
		1	R1/8	23.7	17.6	15	8	19.7	2.5	5.2	19		
	2	R1/4	24.7			11	18.7	2.5		12			
	6	M5	M5×0.8	25.5				3	22.5	2	2	15	
		1	R1/8	25.1	19.5	16	8	21.1	4	13			
	2	R1/4	29.1			11	19		11	18			
	8	3	R3/8	26.1			12	19.7	4		27		
		1	R1/8	29.9			8	25.9	5	17	20		
	2	R1/4	28.6	20.2	17	11	22.6	6	23	20			
	3	R3/8	25.9			12	19.6		26				
	10	1	R1/8	32.3			8	29.3	5	17	35		
		2	R1/4	33.3	23.2	19.5	11	26.3		33			
KKMCS	4	M5	M5×0.8	22.7				2.9	19.7	10	2	12	
		1	R1/8	23.7	17.6	15	8	19.7		4.5	13		
	2	R1/4	26.7			11	20.7	12		2	17		
	6	M5	M5×0.8	25.5				2.9	22.5	12		2	
		1	R1/8	25.1	19.5	16	8	21.1		11	14		
	2	R1/4	29.1			11	23.0		14	23			
	8	1	R1/8	29.9			8	25.9		27			
		2	R1/4	28.6	20.2	17	11	22.6	14	20	25		
	10	1	R1/8	33.3			8	29.3		23	40		
		2	R1/4	31.8	23.2	19.5	11	27.3	17	35	39		
	KKMCL	4	M5	M5×0.8	22.7				2.9	19.6	10	1.5	18
			1	R1/8	23.7	17.6	15	8	19.7	20.7	10	3.5	21
2		R1/4	24.7			11	18.7		14		28		
6		M5	M5×0.8	25.5				3	22.5	12	1.9	26	
		1	R1/8	25.1	19.4	16	8	21.1		9	36		
2		R1/4	29.1			11	23.0		14		28		
8		3	R3/8	29.9			12	22.7		17		49	
		1	R1/8	8	28	31.3						36	
2		R1/4	11	31	32.2	20.2	17	24.8	14	16	41		
3		R3/8	12	32.5	37.8					22.5	67		
10		1	R1/8	8	32.5	38.8	23.2	19.5	29.3	17		69	
		2	R1/4	11	35.5	38.8					30	78	
KKMCL	4	M5	M5×0.8	22.7				2.9	19.7	10	1.5	18	
		1	R1/8	23.7	17.6	15	8	19.7	20.7	10	3.5	21	
	2	R1/4	24.7			11	18.7		14		28		
	6	M5	M5×0.8	25.5				3	22.5	12	1.9	26	
		1	R1/8	25.1	19.4	16	8	21.1		9	36		
	2	R1/4	29.1			11	23.0		14		28		
	8	3	R3/8	29.9			12	22.7		17		49	
		1	R1/8	8	28	31.3						36	
	2	R1/4	11	31	32.2	20.2	17	24.8	14	16	41		
	3	R3/8	12	32.5	37.8					22.5	67		
	10	1	R1/8	8	32.5	38.8	23.2	19.5	29.3	17		69	
		2	R1/4	11	35.5	38.8					30	78	
12	3	R3/8	12	38.5	43				21		113		
	4	R1/2	15	41.5	44.1	26.3	23	33.4	22	39	129		